

Application No.: 09/974040Case No.: 56685US002**Claim Amendments**

1. (presently amended) A co-extruded, uni-axially oriented multi-layer film comprising a co-extruded uni-axially oriented microfiber layer, wherein the film comprises two opposing surfaces, each surface comprising microfibers, and wherein one surface is hydrophilic and one surface is hydrophobic.
2. (original) The film of claim 1 wherein the film is uni-axially oriented by stretching in one direction relatively more than stretching in a perpendicular direction.
3. (canceled)
4. (canceled)
5. (presently amended) The film of claim [[1]]45 comprising two opposing surfaces, one surface comprising microfibers and the other surface not comprising microfibers.
6. (previously presented) The film of claim 5 wherein a film layer having the surface not comprising microfibers exhibits a property selected from the group consisting of elasticity, high or low modulus, puncture resistance, tear resistance, breathability, flame retardancy, high temperature resistance, low temperature resistance, and combinations thereof.
B1
7. (original) The film of claim 1 comprising a microfiber layer and a non-microfiber layer, the microfiber layer comprising a material that exhibits a property selected from the group consisting of hydrophobicity, hydrophilicity, oleophobicity, oleophilicity, a dielectric property, low coefficient of friction, stain resistance, flame retardance, high strength or modulus, an ability to produce a certain size microfiber, and combinations thereof, and
the non-microfiber layer comprising a material selected from the group consisting of a hydrophobic material, a hydrophilic material, an elastomeric material, a tear resistant material, a

Application No.: 09/974040Case No.: 56685US002

puncture resistant material, a high or low temperature resistant material, high strength, high modulus, adhesive properties, and a flame retardant material.

8. (original) The film of claim 7 wherein the microfiber layer comprises a polypropylene.
9. (original) The film of claim 7 wherein the non-microfiber layer comprises an elastomeric polymer.
10. (previously presented) The film of claim 1 wherein the multi-layer film is selected from the group consisting of
a film consisting of two layers and a film consisting of three layers.
11. (original) The film of claim 1 wherein the film comprises a non-microfiber layer comprising a material selected from the group consisting of a polypropylene, a polyethylene, a styrene-ethylene/butylene-styrene block copolymer, a styrene-isoprene-styrene block copolymer, a polyurethane, a fluoropolymer, poly(butylene), poly(isoprene), a nylon, and an adhesive.
B1
CONT.
12. (original) The film of claim 1 wherein the film comprises two microfiber layers sandwiching a non-microfiber layer.
13. (original) The film of claim 12 wherein the non-microfiber layer is elastomeric.
14. (original) The film of claim 12 wherein the non-microfiber layer comprises a material selected from the group consisting of a polypropylene, a polyethylene, a styrene-ethylene/butylene-styrene block copolymer, a styrene-isoprene-styrene block copolymer, a polyurethane, a fluoropolymer, poly(butylene), poly(isoprene), a nylon, and an adhesive.
15. (original) The film of claim 12 wherein a microfiber layer is a semicrystalline polymer selected from the group consisting of high and low density polyethylene, polypropylene, polyoxymethylene, poly(vinylidene fluoride), poly(methyl pentene), poly(ethylene-

Application No.: 09/974040Case No.: 56685US002

chlorotrifluoroethylene), poly(vinyl fluoride), poly(ethylene oxide), poly(ethylene terephthalate), polyethylene naphthalate, poly(butylene terephthalate), poly(lactic acid), nylon 6 12, nylon 6, nylon 66, polybutene, a thermotropic liquid crystal polymer, a blend of one or more of these polymers, or a copolymer of one or more the named monomers.

16. (canceled)

17. (original) The film of claim 1 wherein the film comprises from about 2 to about 5 layers.

18. (original) The film of claim 1 wherein the film comprises from about 2 to about 5 layers, and the total film thickness prior to fibrillation is in the range from about 25 to about 10,160 microns.

19. (presently amended) The film of claim 1 consisting of [[a]]two microfiber layers and a non-microfiber layer.

B,
Cont.

20. (original) The film of claim 1 consisting of 2 microfiber layers.

21. (original) The film of claim 1 consisting of 3 layers: one non-microfiber layer sandwiched by two microfiber layers.

22. (original) The film of claim 1 wherein the microfibers have an average effective diameter of less than 20 microns and a transverse aspect ratio of from 1.5:1 to 20:1.

23. (original) The film of claim 1 wherein the microfibers have an average effective diameter of less than 5 microns.

24. (original) The film of claim 1 wherein the microfibers have an average cross-sectional area of $0.7 \mu^2$ to $2.1 \mu^2$.

Application No.: 09/974040

Case No.: 56685US002

25. (presently amended) A co-extruded multi-layer microfiber article comprising the film of claim 45, comprising two co-extruded microfiber layers and a co-extruded non-microfiber layer comprising a material selected from the group consisting of a polypropylene, a polyethylene, a styrene-ethylene/butylene-styrene block copolymer, a styrene-isoprene-styrene block copolymer, a polyurethane, a fluoropolymer, poly(butylene), poly(isoprene), a nylon, and an adhesive.

26. (original) The article of claim 25 wherein the non-microfiber layer is elastomeric.

27. (previously presented) The article of claim 25 wherein the non-microfiber layer exhibits a property selected from the group consisting of elasticity, high or low modulus, puncture resistance, breathability, flame retardancy, temperature resistance, and combinations thereof.

28. (previously presented) The film of claim 25 wherein a microfiber layer comprises polypropylene.

B1
Cont'd

29. (presently amended) A co-extruded, uni-axially oriented, multi-layer film comprising a co-extruded microfiber-forming layers non-microfiber layer sandwiched between two microfiber-forming layers, wherein one microfiber layer can be microfibrillated to a hydrophilic surface, and one microfiber layer can be microfibrillated to a hydrophobic surface.

30. (presently amended) The film of claim [[29]]45 consisting of two layers.

31. (presently amended) The film of claim [[29]]45 consisting of two microfiber-forming layers.

32. (original) The film of claim 29 consisting of three layers.

33. (canceled)

34. (canceled)

Application No.: 09/974040Case N .: 56685US002

35. (canceled)

36. (original) A multi-layer microfiber article comprising a first microfiber layer at a surface of the article, and second microfiber layer adjacent to the first microfiber-layer, wherein areas of the surface are microfibrillated to form microfibers of only the first layer, and areas of the surface are microfibrillated through the first layer to form microfibers of the second layer.

37. (original) The multi-layer microfiber article of claim 36 wherein a surface of the article includes a pattern comprising a first area of microfibers of one layer of the article, and a second area of microfibers of the second layer.

38. (previously presented) The article of claim 37 wherein an area of microfibers has a property selected from the group consisting of hydrophobicity, hydrophilicity, oleophilicity, and oleophobicity.

*B1
cont* 39-44. (canceled).

45. (previously presented) A multi-layer film comprising two microfiber layers, wherein one microfiber layer is hydrophilic and one microfiber layer is hydrophobic.

46. (presently amended) [[A]]The multi-layer film of claim 45 comprising two microfiber layers sandwiching a non-microfiber layer.

47. (previously presented) The film of claim 46 wherein the non-microfiber layer is elastomeric.

48. (presently amended) The film of claim 46 ~~comprising~~consisting of three layers.

Application N .: 09/974040Case No.: 56685US002

49. (presently amended) The film of claim 46 ~~comprising~~consisting of three coextruded layers.

P1
cont.